




145-AZS24-016

TECHNICAL DATASHEET



Applications...



Construction & Mining
Equipment



Electric & Hybrid
vehicles/equipment



Farm & Agricultural
Equipments



Industrial Automation

Model No.	145-AZS24-016
Rated power (kW)	0.35
Peak power (kW)	1.6
Rated speed (RPM)	3800
Rated voltage (V)	24 VDC
Rated current (Amps)	16 Arms
Peak current (Amps)	48 Arms
Rated torque (Nm)	0.9
Peak torque (Nm)	3
Rated frequency (Hz)	253.33
Torque constant (Nm/Arms)	0.056
Voltage constant (Vrms/rad/s)	0.094
Rotor inertia (Kg/m ² sq)	0.000328
Number of phases	Three Phase
Power factor	≈ 1
Efficiency	Designed for 93%
Winding method	Star/Y
Insulation class	H
Insulation resistance	>500 Mohm at 500 Vdc
Motor type	PM Synchronous
Protection class	>IP64
Winding material	100% Copper
Shaft material	Hardened EN 24
Magnet	NdFeB
Temperature sensor	PT 1000
Max winding sensor temperature	150° C
Core.	Cold Rolled Silicon Steel
Bearings	6206-2Z/C3, 6206-2Z/C3
Cooling	Natural Air Cooled, Forced Air Cool
Weight (Kg)	8 Kg
Mounting	Flange, Foot



INNOTEC POWERSYS PVT. LTD.

Plot No. 67, Block C, DLF Industrial Area, Sector
32, Faridabad, Haryana 121003

USA



+1 202 6181115



info@pmgenerators.com

INDIA



+91 8800101945



sales.india@pmgenerators.com