




Applications...



Construction & Mining
Equipment



Electric & Hybrid
vehicles/equipment



Farm & Agricultural
Equipment



Industrial Automation

Model No.	255-ACZI72-160
Rated power (kW)	13
Peak power (kW)	28.1
Rated speed (RPM)	3200
Rated voltage (V)	72 VDC
Rated current (Amps)	160 Arms
Peak current (Amps)	480 Arms
Rated torque (Nm)	40
Peak torque (Nm)	115.9
Rated frequency (Hz)	213.33
Torque constant (Nm/Arms)	0.25
Voltage constant (Vrms/rad/s)	0.215
Rotor inertia (kg/m ² sq)	0.029484
Number of phases	Three Phase
Power factor	≈ 1
Efficiency	Designed for 93%
Winding method	Star/Y
Insulation class	H
Insulation resistance	>500 Mohm at 500 Vdc
Motor type	PM Synchronous
Protection class	>IP64
Winding material	100% Copper
Shaft material	Hardened EN 24
Magnet	NdFeB
Temperature sensor	PT 1000
Max winding sensor temperature	150° C
Core.	Cold Rolled Silicon Steel
Bearings	6207-2Z/C3, 6207-2Z/C3
Cooling	Natural Air Cooled, Forced Air Cool
Weight (Kg)	55 Kg
Mounting	Flange, Foot