



255-HZI72-250

TECHNICAL DATASHEET



Performance Curves 255-HZI72-250



Applications...



Construction & Mining
Equipments



Electric & Hybrid
vehicles/equipment



Farm & Agricultural
Equipments



Industrial Automation

Model No.	255-HZI72-250
Rated power (kW)	12
Peak power (kW)	24.4
Rated speed (RPM)	5300
Rated voltage (V)	72 VDC
Rated current (Amps)	250 Arms
Peak current (Amps)	750 Arms
Rated torque (Nm)	22.6
Peak torque (Nm)	52.5
Rated frequency (Hz)	353.33
Torque constant (Nm/Arms)	0.091
Voltage constant (Vrms/rad/s)	0.129
Rotor inertia (Kg/m ² sq)	0.010817
Number of phases	Three Phase
Power factor	≈ 1
Efficiency	Designed for 93%
Winding method	Star/Y
Insulation class	H
Insulation resistance	>500 Mohm at 500 Vdc
Motor type	PM Synchronous
Protection class	>IP64
Winding material	100% Copper
Shaft material	Hardened EN 24
Magnet	NdFeB
Temperature sensor	PT 1000
Max winding sensor temperature	150° C
Core.	Cold Rolled Silicon Steel
Bearings	6008-2Z/C3, 6006-2Z/C3
Cooling	Natural Air Cooled, Forced Air Cool
Weight (Kg)	38 Kg
Mounting	Flange, Foot



INNOTEC POWERSYS PVT. LTD.

Plot No. 67, Block C, DLF Industrial Area, Sector
32, Faridabad, Haryana 121003

USA



+1 202 6181115



info@pmgenerators.com

INDIA



+91 8800101945



sales.india@pmgenerators.com