



Performance Curve 360-AZZI72-200



Applications...



Construction & Mining
Equipment



Electric & Hybrid
vehicles/equipment



Farm & Agricultural
Equipment



Industrial Automation

Model No.	360-AZZI72-200
Rated power (kW)	14
Peak power (kW)	38.2
Rated speed (RPM)	1000
Rated voltage (V)	72 VDC
Rated current (Amps)	200 Arms
Peak current (Amps)	600 Arms
Rated torque (Nm)	138.5
Peak torque (Nm)	449.1
Rated frequency (Hz)	133.33
Torque constant (Nm/Arms)	0.692
Voltage constant (V/RPM)	0.062
Rotor inertia (kg/m ² sq)	0.085047
Number of phases	Three Phase
Power factor	≈ 1
Efficiency	Designed for 93%
Winding method	Star/Y
Insulation class	H
Insulation resistance	>500 Mohm at 500 Vdc
Motor type	PM Synchronous
Protection class	>IP64
Winding material	100% Copper
Shaft material	Hardened EN 24
Magnet	NdFeB
Temperature sensor	PT 1000
Max winding sensor temperature	150° C
Core.	Cold Rolled Silicon Steel
Bearings	6215-2Z/C3, 62156-2Z/C3
Cooling	Natural Air Cooled, Forced Air Cool
Weight (Kg)	86 Kg
Mounting	Flange, Foot